

The operating parameters of the battery pack must comply with the technical specification, with particular regard to the operating temperature (20°C). FZLV II system consists of: o batteries ...

The OUT4F module is a universal output device for operation among electrical devices, fire-fighting system and AWEX's Central Battery system. It is designed to operate with the FZLV II system and supplied from its circuits. The OUT4F module has 4 ...

user-friendly central battery system, designed in compliance with the requirements of VDE 0108, PN-EN 50171 and PN-EN 50172 standards. The system provides the possibility of monitoring circuits, luminaires or

The CBS central power supply system is a an advanced, reliable and user-friendly central battery system, designed in compliance with the requirements and all important standards. The system ...

Central battery cabinets are devices made in the form of control enclosures intended for vertical placement on the ground. The doors are equipped with locks preventing unauthorized access to the interior.

Features: o Charging the battery packs in accordance with PN-EN 50-171 o Operation with and control of BST-980 charge boosters o Monitoring of current leakage in final circuits o Protection against deep discharge o Ability to monitor battery voltage symmetry o Fan control o 3 measuring junctions for o Voltage o Current ...

Central battery system provides power supply to the DES luminaires during malfunction due to the use of battery sets. The central battery system has an internal charger which controls charging ...

The LPS is a state-of-the-art, reliable and user-friendly central battery system manufactured by AWEX. It has been designed to meet applicable standards and comprises the proprietary ...

LPS SYSTEM DESCRIPTION The LPS is a state-of-the-art, reliable and user-friendly central battery system manufactured by AWEX. It has been designed to meet applicable standards and comprises the proprietary SMART technology. From the functional point of view, the LPS is equivalent to the CBS, however due to

Central battery system provides power supply to the DES luminaires during malfunction due to the use of battery sets. The central battery system has an internal charger which controls charging process and switching of operation mode. **GENERAL ...**

The CBS central power supply system is a an advanced, reliable and user-friendly central battery system, designed in compliance with the requirements and all important standards. The system provides the

possibility of monitoring circuits, luminaires or both.

The monitoring and power supply systems are a high-tech devices, reliable and easy-to-use central battery systems, constructed in accordance with the requirements of applicable standards and regulations. These systems can ...

The OUT4F module is a universal output device for operation among electrical devices, fire-fighting system and AWEX's Central Battery system. It is designed to operate with the FZLV II ...

user-friendly central battery system, designed in compliance with the requirements of VDE 0108, PN-EN 50171 and PN-EN 50172 standards. The system provides the possibility of monitoring ...

The monitoring and power supply systems are a high-tech devices, reliable and easy-to-use central battery systems, constructed in accordance with the requirements of applicable standards and regulations. These systems can monitor circuits and luminaires in a mixed system.

Features:

- o Charging the battery packs in accordance with PN-EN 50-171
- o Operation with and control of BST-980 charge boosters
- o Monitoring of current leakage in final circuits
- o Protection against deep discharge
- o Ability to monitor ...

Web: <https://ssn.com.pl>

